

Life Cycle Assessment: Results

The following supplementary LCA results are to be read alongside the complete ROCKWOOL® Environmental Product Declaration, attached.

ROCKWOOL® stone wool product:

ROCKLAP H&V Section

The results are for: 1 linear metre of product, with a thickness of 20 mm. Inner diameter of pipe section: 20.9 mm

Limitations

Conservative choices are made in the LCA as described in the ROCKWOOL® Group LCA rules. Therefore, the results can be considered to be conservative and worst case.

Description of the system boundaries (x=included, MNA = Module not assessed)

Pro	duct st	age	Constr instal sta	lation		Use stage					End-of-life stage				
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal
A1	A2	А3	A4	A5	B1	B2	В3	B4	B5	B6	B7	C1	C2	C3	C4
Х	Х	Х	Х	Х	Х	MNA	MNA	MNA	MNA	MNA	MNA	х	Х	Х	Х

ar t	and loads beyond the system boundarie						
Rense-	Recovery-	Recycling-	potential				
D							
)	Κ					

Environmental impact

Parameter	Unit	A1-3	A4	A5	B1	C2	C4	D	
Global warming	kg CO ₂ eqv	3.9E-01	5.9E-02	6.0E-02	0	1.0E-03	4.4E-03	-1.5E-02	
The global warming p unit of that			al contribution to ference gas, carbo						
	ozone is caused	by the breakdov	9.6E-18 h shields the earth wn of certain chlo hen they reach the molecules.	rine and/or bro	omine co	ntaining comp	ounds	-8.2E-16	
Acidification Acid depositions have sources for emission		bstances are ag	•	il fuel combust				-4.9E-05	
Eutrophication	kg PO ₄ ³⁻ eqv	3.0E-04	9.4E-06	1.1E-05	0	2.6E-07	3.2E-06	-6.8E-06	
Excessive enrichme	ent of waters and	continental sur	faces with nutrien	its, and the ass	ociated a	dverse biolog	ical effects.		
Photochemical ozone creation	kg Ethene eqv	8.9E-05	-2.0E-07	3.1E-06	3.2E-11	-1.3E-07	2.1E-06	-5.6E-06	
Chemical reactions brought about by the light energy of the sun. The reaction of nitrogen oxides with hydrocarbons in the presence of sunlight to form ozone is an example of a photochemical reaction.									
Depletion abiotic resources -elements	kg Sb eqv	3.9E-07	4.9E-09	1.2E-09	0	8.5E-11	1.7E-09	-3.3E-09	
Depletion abiotic resources fuels	MJ	4.8E+00	8.0E-01	1.1E-01	0	1.4E-02	6.2E-02	-3.7E-01	
Consumpt	ion of non-renew	able resources,	thereby lowering	their availabili	ty for fut	ure generation	ns.		

ROCKWOOL

Resource use

Parameter	Unit	A1-3	A4	A5	B1	C2	C4	D
Use of renewable primary energy excluding renewable primary energy resources used as raw materials	MJ	1.5E+00	4.5E-01	5.5E-01	0	8.2E-04	8.2E-03	-2.0E-01
Use of renewable primary energy resources used as raw materials	MJ	6.7E-01	0.0E+00	-5.1E-01	0	0.0E+00	0.0E+00	0.0E+00
Total use of renewable primary energy resources	MJ	2.2E+00	4.5E-02	3.9E-02	0	8.2E-04	8.2E-03	-2.0E-01
Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials	MJ	4.3E+00	8.0E-01	1.1E-01	0	1.4E-02	6.4E-02	-3.8E-01
Use of non-renewable primary energy resources used as raw materials	MJ	9.4E-01	0.0E+00	-2.0E-03	0	0.0E+00	0.0E+00	0.0E+00
Total use of non-renewable primary energy resources	MJ	5.2E+00	8.0E-01	1.1E-01	0	1.4E-02	6.4E-02	-3.8E-01
Use of secondary materials	kg	0.0E+00	n/a	0.0E+00	n/a	n/a	n/a	n/a
Use of renewable secondary fuels	MJ	*	*	*	*	*	*	*
Use of non-renewable secondary fuels	MJ	*	*	*	*	*	*	*
Net use of fresh water	m ³	2.0E-03	5.2E-05	1.5E-04	0	8.7E-07	1.6E-05	-1.3E-04

^{*} There are no renewable and no non-renewable secondary fuels used in A3. The minor use of secondary fuels as part of the background datasets is not accounted for.

Waste categories

Parameter	Unit	A1-3	A4	A5	B1	C2	C4	D
Hazardous waste disposed	kg	6.2E-07	3.7E-08	2.5E-09	0	1.4E-09	2.1E-09	-6.7E-10
Non-hazardous waste disposed	kg	3.6E-02	1.2E-04	8.7E-03	0	2.3E-06	3.2E-01	-9.7E-04
Radioactive waste disposed*	kg	1.5E-04	9.9E-07	2.5E-06	0	1.8E-08	7.4E-07	-5.3E-07

^{*} There is never radioactive waste from a ROCKWOOL plant (A3), but there might be small amounts associated with the secondary LCI datasets used for the upstream chain (A1 & A2), which are taken into account here.

Output flows

Parameter	Unit	A1-3	A4	A5	B1	C2	C4	D
Component for re-use	kg	8.25E-08	n/a	2.45E-09	n/a	n/a	n/a	n/a
Materials for recycling	kg	1.45E-02	n/a	n/a	n/a	n/a	n/a	n/a
Materials for energy recovery	kg	1.67E-05	n/a	n/a	n/a	n/a	n/a	n/a

Exported energy MJ n/a n/a n/a n/a n/a n/a

ROCKWOOL FIRESAFE INSULATION

CREATE AND PROTECT®





