

# Life Cycle Assessment: Results

The following supplementary LCA results are to be read alongside the complete ROCKWOOL® Environmental Product Declaration, attached.

ROCKWOOL® stone wool product:

Rocklap H&V Pipe Section

The results are for: 1 linear metre of product, with a thickness of 40 mm. Inner diameter of pipe section: 89 mm

#### Limitations

Conservative choices are made in the LCA as described in the ROCKWOOL® Group LCA rules. Therefore, the results can be considered to be conservative and worst case.

#### Description of the system boundaries (x=included, MNA = Module not assessed)

Prod	duct st	age		ruction lation ige		Use stage						End-of-life stage			
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal
A1	A2	А3	A4	A5	B1	B2	В3	B4	B5	В6	B7	C1	C2	C3	C4
Х	Х	х	Х	Х	Х	MNA	MNA	MNA	MNA	MNA	MNA	Х	Х	х	Х

_		ent	-					
		oad						
		ond						
		/ste						
bo	oun	dar	ie					
	•	2						
Rense-	Recovery-	Recycling-	potential					
D								
Х								

#### **Environmental impact**

Parameter	Unit	A1-3	A4	<b>A</b> 5	B1	C2	C4	D				
Global warming	kg CO <sub>2</sub> eqv	2.2E+00	3.7E-01	3.8E-01	0	6.8E-03	2.8E-02	-9.2E-02				
0	The global warming potential of a gas refers to the total contribution to global warming resulting from the emission of one unit of that gas relative to one unit of the reference gas, carbon dioxide, which is assigned a value of 1.											
	f ozone is caused	by the breakdo	6.1E-17 h shields the earth wn of certain chlo hen they reach the molecules.	rine and/or bro	omine co	ntaining comp	ounds	-5.2E-15				
Acidification Acid depositions has sources for emission		bstances are ag		il fuel combust				-3.1E-04				
Eutrophication  Excessive enrichment	kg PO <sub>4</sub> <sup>3-</sup> eqv ent of waters and	1.9E-03	5.9E-05	7.2E-05	0 ociated a	1.8E-06 adverse biologi	2.1E-05 cal effects.	-4.3E-05				
Photochemical ozone creation Chemical reactions b	•	0 0,	-1.2E-06 of the sun. The re		~	•	1.4E-05 arbons in the	-3.5E-05				
Depletion abiotic resources -elements	kg Sb eqv	1.1E-05	3.1E-08	7.6E-09	0	5.4E-10	1.1E-08	-2.1E-08				
Depletion abiotic resources fuels	MJ	2.7E+01	5.0E+00 thereby lowering	6.6E-01	0	9.2E-02	4.0E-01	-2.3E+00				



#### Resource use

Parameter	Unit	A1-3	A4	A5	B1	C2	C4	D
Use of renewable primary energy excluding renewable primary energy resources used as raw materials	MJ	8.2E+00	2.8E+00	3.5E+00	0	5.3E-03	5.2E-02	-1.3E+00
Use of renewable primary energy resources used as raw materials	MJ	4.2E+00	0.0E+00	-3.2E+00	0	0.0E+00	0.0E+00	0.0E+00
Total use of renewable primary energy resources	MJ	1.2E+01	2.8E-01	2.5E-01	0	5.3E-03	5.2E-02	-1.3E+00
Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials	MJ	2.6E+01	5.0E+00	7.2E-01	0	9.2E-02	4.1E-01	-2.4E+00
Use of non-renewable primary energy resources used as raw materials	MJ	4.1E+00	0.0E+00	-1.3E-02	0	0.0E+00	0.0E+00	0.0E+00
Total use of non-renewable primary energy resources	MJ	3.0E+01	5.0E+00	7.1E-01	0	9.2E-02	4.1E-01	-2.4E+00
Use of secondary materials	kg	0.0E+00	n/a	0.0E+00	n/a	n/a	n/a	n/a
Use of renewable secondary fuels	MJ	*	*	*	*	*	*	*
Use of non-renewable secondary fuels	MJ	*	*	*	*	*	*	*
Net use of fresh water	m <sup>3</sup>	1.0E-02	3.3E-04	9.2E-04	0	5.5E-06	1.0E-04	-8.4E-04

<sup>\*</sup> There are no renewable and no non-renewable secondary fuels used in A3. The minor use of secondary fuels as part of the background datasets is not accounted for.

## Waste categories

Parameter	Unit	A1-3	A4	A5	B1	C2	C4	D
Hazardous waste disposed	kg	3.5E-06	2.4E-07	1.5E-08	0	1.0E-08	1.6E-08	-4.2E-09
Non-hazardous waste disposed	kg	1.7E-01	7.7E-04	5.5E-02	0	1.5E-05	2.0E+00	-6.1E-03
Radioactive waste disposed*	kg	6.3E-04	6.2E-06	1.6E-05	0	1.1E-07	4.8E-06	-3.4E-06

<sup>\*</sup> There is never radioactive waste from a ROCKWOOL plant (A3), but there might be small amounts associated with the secondary LCI datasets used for the upstream chain (A1 & A2), which are taken into account here.

### **Output flows**

Parameter	Unit	A1-3	A4	<b>A</b> 5	B1	C2	C4	D
Component for re-use	kg	5.20E-07	n/a	1.55E-08	n/a	n/a	n/a	n/a
Materials for recycling	kg	9.16E-02	n/a	n/a	n/a	n/a	n/a	n/a
Materials for energy recovery	kg	1.05E-04	n/a	n/a	n/a	n/a	n/a	n/a

Exported energy MJ n/a n/a n/a n/a n/a n/a

ROCKWOOL FIRESAFE INSULATION

CREATE AND PROTECT®





