

Life Cycle Assessment: Results

The following supplementary LCA results are to be read alongside the complete ROCKWOOL® Environmental Product Declaration, attached.

ROCKWOOL® stone wool product:

ROCKLAP H&V Section

The results are for: 1 linear metre of product, with a thickness of 40 mm. Inner diameter of pipe section: 52.5 mm

Limitations

Conservative choices are made in the LCA as described in the ROCKWOOL® Group LCA rules. Therefore, the results can be considered to be conservative and worst case.

Description of the system boundaries (x=included, MNA = Module not assessed)

		•		,				`		•						,	
Product stage			instal	ruction llation age		Use stage							End-of-life stage				
	Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-
	A1	A2	А3	A4	A5	B1	B2	В3	B4	B5	В6	B7	C1	C2	C3	C4	
	Х	Х	х	Х	Х	Х	MNA	MNA	MNA	MNA	MNA	MNA	Х	Х	Х	Х	

RecoveryA RecoveryBecoveryBecoveryColingDotential

Environmental impact

Parameter	Unit	A1-3	A4	A5	B1	C2	C4	D		
Global warming	kg CO ₂ eqv	1.5E+00	2.7E-01	2.7E-01	0	4.6E-03	1.9E-02	-6.6E-02		
The global warming p unit of that										
Ozone depletion kg CFC11 eqv 3.7E-09 4.3E-17 4.1E-10 0 1.8E-16 1.0E-14 Destruction of the stratospheric ozone layer which shields the earth from ultraviolet radiation harmful to life. This destruction of ozone is caused by the breakdown of certain chlorine and/or bromine containing compounds (chlorofluorocarbons or halons), which break down when they reach the stratosphere and then catalytically destroy ozone molecules.										
Acidification $kg SO_2$ eqv 5.9E-03 2.1E-04 1.5E-04 0 4.4E-06 1.2E-04 Acid depositions have negative impacts on natural ecosystems and the man-made environment incl, buildings. The main sources for emissions of acidifying substances are agriculture and fossil fuel combustion used for electricity production, heating and transport.										
Eutrophication Excessive enrichme	kg PO ₄ ³⁻ eqv	1.3E-03	4.2E-05	5.2E-05	0	9.7E-07	1.4E-05	-3.1E-05		
		Continental sur	iaces with nutrier	its, and the ass	ociateu a	daverse biolog	icai effects.			
Photochemical ozone creation	kg Ethene eqv	3.3E-04	-8.9E-07	1.4E-05	1.4E-10	-3.7E-07	9.2E-06	-2.5E-05		
Chemical reactions brought about by the light energy of the sun. The reaction of nitrogen oxides with hydrocarbons in the presence of sunlight to form ozone is an example of a photochemical reaction.										
Depletion abiotic kg Sb eqv 1.1E-06 2.2E-08 5.5E-09 0 3.7E-10 7.3E-09 resources -elements										
Depletion abiotic resources fuels	MJ	1.8E+01	3.6E+00	4.8E-01	0	6.2E-02	2.7E-01	-1.7E+00		
Consumption of non-renewable resources, thereby lowering their availability for future generations.										

ROCKWOOL

Resource use

11030df0C d3C								
Parameter	Unit	A1-3	A4	A5	B1	C2	C4	D
Use of renewable primary energy excluding renewable primary energy resources used as raw materials	MJ	5.6E+00	2.0E+00	2.5E+00	0	3.5E-03	3.6E-02	-9.1E-01
Use of renewable primary energy resources used as raw materials	MJ	3.0E+00	0.0E+00	-2.3E+00	0	0.0E+00	0.0E+00	0.0E+00
Total use of renewable primary energy resources	MJ	8.7E+00	2.0E-01	1.8E-01	0	3.6E-03	3.6E-02	-9.1E-01
Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials	MJ	1.6E+01	3.6E+00	5.2E-01	0	6.2E-02	2.8E-01	-1.7E+00
Use of non-renewable primary energy resources used as raw materials	MJ	3.1E+00	0.0E+00	-9.0E-03	0	0.0E+00	0.0E+00	0.0E+00
Total use of non-renewable primary energy resources	MJ	1.9E+01	3.6E+00	5.1E-01	0	6.2E-02	2.8E-01	-1.7E+00
Use of secondary materials	kg	0.0E+00	n/a	0.0E+00	n/a	n/a	n/a	n/a
Use of renewable secondary fuels	MJ	*	*	*	*	*	*	*
Use of non-renewable secondary fuels	MJ	*	*	*	*	*	*	*
Net use of fresh water	m ³	6.6E-03	2.4E-04	6.6E-04	0	3.9E-06	6.9E-05	-6.0E-04

^{*} There are no renewable and no non-renewable secondary fuels used in A3. The minor use of secondary fuels as part of the background datasets is not accounted for.

Waste categories

Parameter	Unit	A1-3	A 4	A5	B1	C2	C4	D
Hazardous waste disposed	kg	1.5E-06	1.7E-07	1.1E-08	0	4.4E-09	6.8E-09	-3.0E-09
Non-hazardous waste disposed	kg	1.1E-01	5.5E-04	3.9E-02	0	9.8E-06	1.4E+00	-4.4E-03
Radioactive waste disposed*	kg	3.6E-04	4.5E-06	1.1E-05	0	7.8E-08	3.2E-06	-2.4E-06

^{*} There is never radioactive waste from a ROCKWOOL plant (A3), but there might be small amounts associated with the secondary LCI datasets used for the upstream chain (A1 & A2), which are taken into account here.

Output flows

Parameter	Unit	A1-3	A4	A5	B1	C2	C4	D
Component for re-use	kg	3.73E-07	n/a	1.11E-08	n/a	n/a	n/a	n/a
Materials for recycling	kg	6.57E-02	n/a	n/a	n/a	n/a	n/a	n/a
Materials for energy recovery	kg	7.53E-05	n/a	n/a	n/a	n/a	n/a	n/a

Exported energy MJ n/a n/a n/a n/a n/a n/a

ROCKWOOL FIRESAFE INSULATION

CREATE AND PROTECT®





