

Life Cycle Assessment: Results

The following supplementary LCA results are to be read alongside the complete ROCKWOOL® Environmental Product Declaration, attached.

ROCKWOOL® stone wool product:

RWA45

The results are for: 1 m2 of product,

with a thickness of

25 mm.

Thermal resistance as stated in product data sheet.

Limitations

Conservative choices are made in the LCA as described in the ROCKWOOL® Group LCA rules. Therefore, the results can be considered to be conservative and worst case.

Description of the system boundaries (x=included, MNA = Module not assessed)

Pro	duct st	age	Constr instal sta	lation		Use stage					End-of-life stage				
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal
A1	A2	А3	A4	A5	B1	B2	В3	B4	B5	B6	B7	C1	C2	C3	C4
Х	Х	х	Х	Х	Х	MNA	MNA	MNA	MNA	MNA	MNA	х	Х	х	х

_	en		-					
	nd I							
	bey							
	e sy							
bo	oun	daı	ie					
	•	2						
Rense-	Recovery-	Recycling-	potential					
D								
Х								

Environmental impact

Parameter	Unit	A1-3	A4	A5	B1	C2	C4	D
Global warming	kg CO ₂ eqv	1.8E+00	2.1E-01	2.2E-01	0	4.3E-03	1.8E-02	-5.3E-02
The global warming punit of that	· ·		al contribution to ference gas, carbo	•	~	•		
	f ozone is caused	by the breakdov	3.5E-17 In shields the earth In of certain chlo In they reach the molecules.	rine and/or bro	mine co	ntaining comp	ounds	-3.0E-15
Acidification Acid depositions have sources for emission		bstances are ag		il fuel combust				-1.8E-04
Eutrophication	kg PO ₄ 3- eqv	1.3E-03	3.4E-05	4.2E-05	0	1.5E-06	1.3E-05	-2.5E-05
Excessive enrichme	ent of waters and	continental sur	faces with nutrien	nts, and the asso	ociated a	dverse biolog	ical effects.	
Photochemical ozone creation	kg Ethene eqv	4.2E-04	-7.2E-07	1.1E-05	1.2E-10	-1.2E-06	8.9E-06	-2.0E-05
Chemical reactions brought about by the light energy of the sun. The reaction of nitrogen oxides with hydrocarbons in the presence of sunlight to form ozone is an example of a photochemical reaction.								
Depletion abiotic resources -elements	kg Sb eqv	1.1E-05	1.8E-08	4.4E-09	0	3.3E-10	6.9E-09	-1.2E-08
Depletion abiotic resources fuels	MJ	2.2E+01	2.9E+00	3.8E-01	0	5.8E-02	2.5E-01	-1.3E+00
Consumpt	tion of non-renew	able resources,	thereby lowering	their availabili	ty for fut	ure generation	ns.	



Resource use

Parameter	Unit	A1-3	A4	A5	B1	C2	C4	D
Use of renewable primary energy excluding renewable primary energy resources used as raw materials	MJ	6.3E+00	1.6E+00	2.0E+00	0	3.4E-03	3.2E-02	-7.4E-01
Use of renewable primary energy resources used as raw materials	MJ	2.4E+00	0.0E+00	-1.9E+00	0	0.0E+00	0.0E+00	0.0E+00
Total use of renewable primary energy resources	MJ	8.8E+00	1.6E-01	1.4E-01	0	3.5E-03	3.2E-02	-7.4E-01
Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials	MJ	2.1E+01	2.9E+00	4.2E-01	0	5.8E-02	2.6E-01	-1.4E+00
Use of non-renewable primary energy resources used as raw materials	MJ	4.0E+00	0.0E+00	-7.3E-03	0	0.0E+00	0.0E+00	0.0E+00
Total use of non-renewable primary energy resources	MJ	2.5E+01	2.9E+00	4.1E-01	0	5.8E-02	2.6E-01	-1.4E+00
Use of secondary materials	kg	0.0E+00	n/a	0.0E+00	n/a	n/a	n/a	n/a
Use of renewable secondary fuels	MJ	*	*	*	*	*	*	*
Use of non-renewable secondary fuels	MJ	*	*	*	*	*	*	*
Net use of fresh water	m ³	9.8E-03	1.9E-04	5.3E-04	0	3.2E-06	6.2E-05	-4.8E-04

^{*} There are no renewable and no non-renewable secondary fuels used in A3. The minor use of secondary fuels as part of the background datasets is not accounted for.

Waste categories

Parameter	Unit	A1-3	A4	A5	B1	C2	C4	D
Hazardous waste disposed	kg	4.4E-06	1.4E-07	9.0E-09	0	9.9E-09	1.6E-08	-2.4E-09
Non-hazardous waste disposed	kg	1.7E-01	4.5E-04	3.2E-02	0	9.8E-06	1.3E+00	-3.6E-03
Radioactive waste disposed*	kg	8.5E-04	3.6E-06	9.1E-06	0	7.3E-08	3.1E-06	-2.0E-06

^{*} There is never radioactive waste from a ROCKWOOL plant (A3), but there might be small amounts associated with the secondary LCI datasets used for the upstream chain (A1 & A2), which are taken into account here.

Output flows

Parameter	Unit	A1-3	A4	A5	B1	C2	C4	D
Component for re-use	kg	3.01E-07	n/a	8.96E-09	n/a	n/a	n/a	n/a
Materials for recycling	kg	5.30E-02	n/a	n/a	n/a	n/a	n/a	n/a
Materials for energy recovery	kg	6.08E-05	n/a	n/a	n/a	n/a	n/a	n/a

Exported energy MJ n/a n/a n/a n/a n/a n/a

ROCKWOOL FIRESAFE INSULATION

CREATE AND PROTECT®





