

Life Cycle Assessment: Results

The following supplementary LCA results are to be read alongside the complete ROCKWOOL® Environmental Product Declaration, attached.

ROCKWOOL® stone wool product:

ROCKLAP H&V Section

The results are for: 1 linear metre of product, with a thickness of 25 mm. Inner diameter of pipe section: 67 mm

Limitations

Conservative choices are made in the LCA as described in the ROCKWOOL® Group LCA rules. Therefore, the results can be considered to be conservative and worst case.

Description of the system boundaries (x=included, MNA = Module not assessed)

Pro	duct st	age	Constr instal sta			Use stage					End-of-life stage					
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	ď
A1	A2	А3	A4	A5	B1	B2	В3	B4	B5	B6	B7	C1	C2	C3	C4	
Х	х	х	Х	Х	х	MNA	MNA	MNA	MNA	MNA	MNA	Х	Х	х	Х	ı

the system pondarie

ReusePecoveryRecyclingPotential

and loads beyond

Environmental impact

Parameter	Unit	A1-3	A4	A5	B1	C2	C4	D
Global warming	kg CO ₂ eqv	1.2E+00	1.6E-01	1.7E-01	0	3.3E-03	1.4E-02	-4.1E-02
The global warming p unit of that	•		al contribution to ference gas, carbo	•	· ·	•		
	ozone is caused	by the breakdov	2.7E-17 h shields the earth wn of certain chlo hen they reach th molecules.	rine and/or bro	omine co	ntaining comp	ounds	-2.3E-15
Acidification Acid depositions have sources for emission		ıbstances are ag	•	il fuel combust				-1.4E-04
Eutrophication	kg PO ₄ ³⁻ eqv	9.3E-04	2.6E-05	3.2E-05	0	1.1E-06	1.0E-05	-1.9E-05
Excessive enrichme	ent of waters and	continental sur	faces with nutrier	nts, and the ass	ociated a	dverse biolog	cal effects.	
Photochemical ozone creation	kg Ethene eqv	2.9E-04	-5.5E-07	8.7E-06	9.0E-11	-8.6E-07	6.8E-06	-1.6E-05
Chemical reactions brought about by the light energy of the sun. The reaction of nitrogen oxides with hydrocarbons in the presence of sunlight to form ozone is an example of a photochemical reaction.								
Depletion abiotic resources -elements	kg Sb eqv	1.0E-05	1.4E-08	3.4E-09	0	2.5E-10	5.2E-09	-9.2E-09
Depletion abiotic resources fuels	MJ	1.5E+01	2.2E+00	3.0E-01	0	4.4E-02	1.9E-01	-1.0E+00
Consumpt	ion of non-renew	able resources,	thereby lowering	their availabili	ty for fut	ure generation	ns.	



Resource use

Parameter	Unit	A1-3	A 4	A5	B1	C2	C4	D
Use of renewable primary energy excluding renewable primary energy resources used as raw materials	MJ	4.2E+00	1.3E+00	1.5E+00	0	2.6E-03	2.5E-02	-5.7E-01
Use of renewable primary energy resources used as raw materials	MJ	1.9E+00	0.0E+00	-1.4E+00	0	0.0E+00	0.0E+00	0.0E+00
Total use of renewable primary energy resources	MJ	6.1E+00	1.3E-01	1.1E-01	0	2.6E-03	2.5E-02	-5.7E-01
Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials	MJ	1.5E+01	2.2E+00	3.2E-01	0	4.4E-02	2.0E-01	-1.1E+00
Use of non-renewable primary energy resources used as raw materials	MJ	2.2E+00	0.0E+00	-5.6E-03	0	0.0E+00	0.0E+00	0.0E+00
Total use of non-renewable primary energy resources	MJ	1.7E+01	2.2E+00	3.2E-01	0	4.4E-02	2.0E-01	-1.1E+00
Use of secondary materials	kg	0.0E+00	n/a	0.0E+00	n/a	n/a	n/a	n/a
Use of renewable secondary fuels	MJ	*	*	*	*	*	*	*
Use of non-renewable secondary fuels	MJ	*	*	*	*	*	*	*
Net use of fresh water	m^3	6.2E-03	1.5E-04	4.1E-04	0	2.5E-06	4.8E-05	-3.7E-04

^{*} There are no renewable and no non-renewable secondary fuels used in A3. The minor use of secondary fuels as part of the background datasets is not accounted for.

Waste categories

Parameter	Unit	A1-3	A4	A5	B1	C2	C4	D
Hazardous waste disposed	kg	2.8E-06	1.0E-07	6.9E-09	0	7.3E-09	1.2E-08	-1.9E-09
Non-hazardous waste disposed	kg	1.0E-01	3.4E-04	2.4E-02	0	7.5E-06	9.8E-01	-2.7E-03
Radioactive waste disposed*	kg	4.6E-04	2.8E-06	7.0E-06	0	5.6E-08	2.4E-06	-1.5E-06

^{*} There is never radioactive waste from a ROCKWOOL plant (A3), but there might be small amounts associated with the secondary LCI datasets used for the upstream chain (A1 & A2), which are taken into account here.

Output flows

Parameter	Unit	A1-3	A4	A5	B1	C2	C4	D
Component for re-use	kg	2.32E-07	n/a	6.90E-09	n/a	n/a	n/a	n/a
Materials for recycling	kg	4.08E-02	n/a	n/a	n/a	n/a	n/a	n/a
Materials for energy recovery	kg	4.68E-05	n/a	n/a	n/a	n/a	n/a	n/a

Exported energy MJ n/a n/a n/a n/a n/a n/a

ROCKWOOL FIRESAFE INSULATION

CREATE AND PROTECT®





